



(A) (B)

ITEM No.	PART NO.	DESCRIPTION	MATERIAL	MATERIAL STANDARD
1	290553	SHUT TARGET	PLASTIC	ZYTEL
2	290552	OPEN TARGET	PLASTIC	ZYTEL
3	198429	COTTER PIN (SHORT)	BRASS	ASTM B21
4	147446	COUPLING	CAST IRON	ASTM A126 CLASS B
5	198430	COTTER PIN (LONG)	BRASS	ASTM B21
6	290157	RETAINING RING	STAINLESS STEEL	AISI 302
7	195040	HEX BOLT	STAINLESS STEEL	
8	148689	BELL	CAST IRON	ASTM A126 CL.B
9	195049	HEX NUT	STAINLESS STEEL	ASTM A563 GR.A
10	148691	OPERATING NUT	DUCTILE IRON	ASTM A536 GR.65-45-12
11	290143	CAP	POLYPROPYLENE	
12	190330	SPRING PIN	STAINLESS STEEL	AISI 420
13	241011	THREADED SLEEVE	ALUMINUM	ALLOY 319
14	148633	UPPER STEM	STEEL	ASTM A513
15	198582	PIPE PLUG - HEX SOCKET	STEEL/ZINC PLATED	ASTM A307 GR.A
16	241092	POST HEAD	CAST IRON	ASTM A126 CL.B
17	148790	WINDOW	MOLDED PLASTIC	
18	049922	HEX HEAD SCREW	STEEL/ZINC PLATED	ASTM A307 GR.A
19	147308	LOWER BARREL	DUCTILE IRON	ASTM A746 CLASS 51
20	147307	UPPER BARREL	STEEL	ASTM A53 GR.B
21	241013	WRENCH	STEEL	ASTM A36 H.R.S.
22	290426	LOWER STEM	STEEL	ASTM A500 GR.B
23	198428	SPLINE SET SCREW	STEEL	ANSI B18.3
24	290164	SHIPPING DISC *	PRESS BOARD	
25	198429	COTTER PIN SHORT *	BRASS	ASTM B21
26	198430	COTTER PIN LONG *	BRASS	ASTM B21

* ITEMS NOT SHOWN

VALVE SIZE	NOMINAL TRENCH DEPTHS FOR MUELLER RESILIENT WEDGE POST INDICATOR VALVES																	
	ORDER LENGTH "A"		ORDER LENGTH "B"		ORDER LENGTH "C"		ORDER LENGTH "D"		ORDER LENGTH "E"		ORDER LENGTH "F"		ORDER LENGTH "G"		ORDER LENGTH "H"		ORDER LENGTH "I"	
	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.
16"	5'-3"	7'-1"	6'-10"	8'-10"	8'-7"	10'-7"	10'-2"	11'-11"	12'-1"	13'-10"	13'-10"	15'-10"	16'-0"	18'-0"	17'-8"	19'-8"	19'-4"	21'-4"
18"	5'-10"	7'-8"	7'-5"	9'-5"	9'-2"	11'-2"	10'-11"	12'-6"	12'-8"	14'-5"	14'-5"	16'-5"	16'-7"	18'-7"	18'-3"	20'-3"	19'-11"	21'-11"
20"	6'-3"	8'-1"	7'-9"	9'-10"	9'-6"	11'-7"	11'-3"	12'-11"	13'-0"	14'-10"	14'-9"	16'-10"	16'-11"	19'-0"	18'-7"	20'-8"	20'-3"	22'-4"
24"	6'-11"	8'-9"	8'-6"	10'-6"	10'-3"	12'-3"	12'-0"	13'-7"	13'-9"	15'-6"	15'-6"	17'-6"	17'-8"	19'-8"	19'-4"	21'-4"	21'-0"	23'-0"

C20807

REV.	DESCRIPTION	REF.	DRFT'R	CHK'R	APP	DATE
B	REVISED SALES CHART PER FORM F12111C Rev 6/14	-----	ANC			11-13-15
A	REMOVE SALES CHART	EO 3261	ANC			9-1-11

(MILLIMETER) INCH INITIAL RELEASE DRFT'R ANC 7-27-11 CHK'R MDW 7-27-11 APP MDW 7-27-11 E.O. NUMBER EO 3252-1	TOLERANCES - MACHINING UNLESS OTHERWISE NOTED BREAK EDGES FINISH SURFACES MACH. .006/.016		THIRD ANGLE PROJECTION PURCH. FINISH	
	FRACTIONS DECIMALS ANGLES ±1/64 2 PL ±.025 3 PL ±.010 ±1°		REF. NO. SCALE STK. NO.	
Mueller Canada		MAT'L. DESCR. 16"-24" VERTICAL ADJUSTABLE INDICATOR POST ASSEMBLY WITH DUCTILE LOWER BARREL		REVISION B NUMBER C20807 SHEET 1 OF 1